

CHOOSING YOUR GMT POLE.

First take the “J” measurement on your boat. To do this you should measure on deck from the front of the mast to the head stay fitting. This is your “J” measurement. In most cases this will be your approximate pole length. Now from the matrix below choose the appropriate pole.

Pole model #	3L	3S	4L	4S	5L	5S	6S
Pole diameter ID	3.0”	3.0”	4.0”	4.0”	5.0”	5.0”	6.0”
Tube weight/foot(lbs.)	0.55	0.69	0.76	0.92	1.1	1.3	1.7
Equivalent alloy tube	3.0”	3.5”	4.0”	4.5”	5.0”	5.5”	6.5”
Max. pole length(SPL in ft.)	13.0	15.0	18.0	19.0	24.0	28.0	34.0
Typical boat size	J30	J35	J44	LH53	SW51	S68	S77

Includes paint Or clear finish and hardware installation. Add end fittings.

Bare Tube: cut to length, no paint/fittings/holes drilled:

Painted tube: cut to length, no fittings/holes drilled:

Forespar End Fittings:

TS(I)	ok	ok	ok	ok	ok	ok
GP(O)	ok	ok	ok	ok	ok	ok
UTS (I)	ok	ok	ok	ok		
UGP (O)	ok	ok	ok	ok		
TR(O or I)UTR	ok	ok	ok			
EL or UXP(O or I)	ok	ok				

Sparcraft End Fittings:

Intrepid II (O)	All sizes
Inboard end stub	All sizes

Hall End Fittings:

Quick Trip (O)	All sizes to 5”
Quick Connect	Not recommended for 6” poles

I – Inboard
O = Outboard

Revised 2/08